


tSENSE (Disp)

CO₂-, Temperature- and RH-
Transmitter with colour touch display



CO ₂	1205ppm
Temperature	73.6°F
Humidity	72%RH
	



tSENSE is an advanced and versatile 3-in-1 transmitter designed for installation in the air-conditioned zone. It measures CO₂ concentration, temperature and humidity in the ambient air accurately without need for additional compensation – true read. The data transmits to a BMS system or stand-alone controller using industry standard output signals and communication protocols.

tSENSE combines all the necessary elements for effective climate control in commercial office buildings, hospitals, hotels, schools and other facilities. Using CO₂-monitoring for demand control ventilation (DCV) allows healthy, comfortable and cost-effective environment for the occupants. It is flexible in design with temperature control and combination of humidity control optional. Though suitable for use in many different energy-efficient ventilation strategies, **Senseair®** welcomes any discussions for specific needs.

Complies with ASHRAE standard 189.1
(±50ppm @ 1000ppm of measured CO₂ value)

STANDARD SPECIFICATION

Measured gas	Carbon dioxide (CO ₂)
Operating principle	Non-dispersive infrared (NDIR)
Measurement range	0–2000ppm
OUT1 CO ₂	0–10VDC, 0–2000ppm
OUT2 Temperature	0–10VDC, 0–50°C
OUT3 Relative Humidity	0–10VDC, 0–100%RH
Accuracy (CO ₂)	±30ppm ±3% of reading
Dimensions	125mm x 85mm x 22mm
Dimensions display	49mm x 37mm
Life expectancy	>15 years
Operation temperature range	0–50°C
Power supply	12VDC, 24VAC/DC
Communication	Modbus (MB) or BACnet (BAC) protocol over RS485

KEY BENEFITS

- Maintenance free
- 3 sensors in one housing
- Colour touch display with possibility of customisable GUI
- Flexibility - Temperature and/or Humidity optional
- Improved housing design for effective measurement

General Performance:

Storage Temperature Range-30–70°C
 Sensor Life Expectancy¹>15 years
 Maintenance Interval²Maintenance free
 Self-DiagnosticsComplete function-check of the sensor module
 Display (Disp)Configurable colour LCD with CO₂ (ppm), Temperature (°C) and Humidity (%RH)
 Buttons.....Touch display (Disp)
 Warm-up Time≤1min.(@ full specs 15min)
 Operating Temperature Range0–50°C
 Operating Humidity Range0–95%RH, non condensing humidity environment
 Operating EnvironmentResidential, commercial

Electrical / Mechanical:

Power Input.....12VDC, 24VDC or 24VAC (50–60Hz) ±20%
 Power Consumption.....<0.35W average non-display version, <0.6W display version
 Peak Power Consumption.....<2W
 Wiring ConnectionsScrew terminal, max 1.5mm², Containing: Power, GND, Out1, Out2, Out3, RS485. Option: passive temperature or relay

CO₂ Measurement:

Sensing MethodNon-dispersive infrared (NDIR) waveguide technology
 Sampling MethodDiffusion
 Response Time (T_{1/e})<3min
 Measurement Range0–2000ppm_{vol}.
 Accuracy³±50ppm (@1000ppm_{vol}, 17–28°C and 30–60%RH)
 Typical full range: ±30ppm +3% of measured value^{4, 5}
 Pressure Dependence.....+1.58% reading per kPa deviation from normal pressure, 101.3kPa
 Measurement Interval.....15s

Temperature Measurement:

Measurement Range (T)0–50°C
 Accuracy⁶±0.5°C (@ 17–28°C), ±1.0°C (@ 0–50°C)
 Repeatability±0.25°C (@ 17–28°C)
 Response Time.....<6min (Air velocity of 0.15m/s)
 Measurement Interval.....15s

Relative Humidity Measurement:

Measurement Range.....0–100%RH
 Accuracy⁶±5%RH (@ 20–80%RH)
 Hysteresis±1%RH (@ 20–80%RH)
 Annual Drift<±0.5%RH
 Repeatability±0.25%RH (@ 17–28°C)
 Response Time.....<6min (Air velocity of 0.15m/s)
 Measurement Interval.....15s

Outputs:

Linear Analog Outputs:

Protection.....PTC-fuses (auto reset), short-circuit safe
 Output Conversion Accuracy.....±2% of reading ±20mV
 Output SignalVoltage output 0–10V, R_{out} <100Ω, Load: >5kΩ
 Output Resolution10-bits, 10mV steps, 0.1% steps of full ppm/°C/%RH range
 Out1: CO₂⁷0–10V, corresponds to 0–2000ppm_{vol}, at screw terminal
 Out2: Temperature (T)⁷0–10V, corresponds to 0–50°C, at screw terminal
 Out3: Relative Humidity (RH)⁷0–10V, corresponds to 0–100%RH, at screw terminal

Digital Output:

Relay (RL)⁷On ≥1000ppm_{vol} CO₂, Off ≤900ppm_{vol}, CO₂, at screw terminal
 Form C / DPDT, I_{max}: 1A/50VAC/24VDC
 Input Source.....CO₂/T/RH (configurable via touch display)

tSENSE Serie

Art.Nr.	Produkt	Zusätzliche Funktionen
070-8-0001	tSENSE Disp T RH RL MB BAC	with display
070-8-0002	tSENSE T RH RL MB BAC	no display
070-8-0003	tSENSE VAV Disp TrH RL Modbus Bacnet	with display

¹ SO₂ enriched environments are excluded.

² No maintenance required in normal indoor air as ABC (Automatic Baseline Calibration) is used.

³ In normal IAQ applications, accuracy is defined after minimum three (3) ABC-periods of continuous operation with ABC.

⁴ Accuracy is specified over operating temperature range. Specification is referenced to certified calibration mixtures. Uncertainty of calibration gas mixtures (±1% currently) is to be added to the specified accuracy for absolute measurements.

⁵ Repeatability is included. Uncertainty of calibration gases (±1%) is added to the specified accuracy.

⁶ Depending on display brightness setting.

⁷ Can be configured with PC software UIP (version 5 or later). See information at senseair.com